

ADDITIVES

SMOOTH OPERATOR

Food grade conveyor lubricant

Properties

SMOOTH OPERATOR is a water-based, food grade conveyor lubricant. The dual property of this lubricant ensures and provides excellent glass to surface lubricity with moderate foam. Even under adverse conditions. This dual functionality makes molecules more attractive to glass, plastic, and metal surfaces creating a chemical protection barrier, inhibiting corrosion. The superior hard water tolerance of SMOOTH OPERATOR expands its versatility in hard water regions of the country.

Applications

SMOOTH OPERATOR can be used for a variety of conveyor lubricant applications, contact your ATPGroup representative for more information.

Physical Properties

Color	Colorless, clear
Scent	Cooking oil-like odor
Density (20 °C)	1.02 g/mL
pH	10-11.5

Directions for Use

One ounce per gallon or two gallons depending on water hardness. Consult your ATPGroup representative for specific use procedures and instructions.

Packaging

This product is available in 5 gal pails, 55 gal drums, and 265 gal totes. Other sizes available on request.

Transport (DOT)

Non-regulated material.

Important: Read and understand label and Safety Data Sheet (SDS) for complete listing of hazards, precautions, first aid statements, and storage and handling information. SDS are available from the distributor of this product. 24-Hour Emergency Response Line 1-800-255-3924.